

Pro50 STARTER

A Great way to get into the Business

Lightweight and portable. Won't break the bank.



33 ft x 1 in. and
16 ft x 1 in. material hoses

50 ft. x 1/2 in. air line

Pump Specifications

Hopper capacity	12.5 gallons
Loading height	25"
Motor rating	1-3/4 h.p., 110v 18 amp.
Generator Required (pump, mixer & air compr.)	7.5 kw w/26amp surge startup
Stator screw rpm	variable rheostat control 8-140 rpm
Material flow rate	2 to 3.5 gallons a minute
Max. pumping distance	3/4" hose - 50 ft./1" hose-85 ft.
Weight	150 lbs.

OPERATING DIMENSIONS (boxed)

Length	44" (50")
Width	20" (25")
Height	36" (40")


Mixer Specifications

Drum capacity	4.5 cu. ft.
Batch output	3.0 cu. ft.
Motor rating	2 HP 110V, 17 amp
Paddle speed	38 rpm
Drum diameter	30"
Machine weight (boxed)	286lbs (310 lbs)
Wheel size	10"

OPERATING DIMENSIONS (boxed)

Length	33" (36")
Height	45-50" (46")
Width	29 (32")

An onboard computer balances the spray rate with the pumping volume, this prevents clogging.



Mortar spray gun



The accessory diaphragm compressor delivers high volume output with low pressure. This ensures complete and even material application when spraying.